

## TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

### BRAYT T4 PROTECT LIQUID > silicone free <



#### PRODUCT DESCRIPTION

BRAYT T4 Protect liquid is a fine – grained polishing paste to refresh the surface which leave an invisible protection film against the contamination. Increase the paint life by 40 – 50% and reduce dirt accumulation by 70 – 80%. Applicable for protection on painted surfaces, gelcoat and polycarbonate. Also has a slightly abrasive properties that allow you to remove minimum size defects and holograms. Is suitable for gelcoat and all automotive paints including Acrylic, two-component, single-component, water-based and OEM. Can also be used for ceramic anti-scratch paints. Increases paint gloss and protect against UV rays, acid rain, tree resins, insects and oxidation. Applied by hand or eccentric polishing machine with polishing sponge. For high glossy finish without haze and holograms use soft polishing sponge.

---

#### TROTON Sp. z.o.o

Address: Ząbrowo 14A, 78-120 Gościno, Poland, Tel: +48 94 35 123 94  
Tel/Fax: +48 94 35 126 22 Website: [www.troton.com.pl](http://www.troton.com.pl) Email: [troton@troton.com.pl](mailto:troton@troton.com.pl)

**PHYSICAL AND CHEMICAL PROPERTIES**

- Composition: emulsion
- Appearance: fluid gel
- Capacity: 250 ml ; 500 ml ; 1 l
- Viscosity: > 130 mm<sup>2</sup>/s
- Specific gravity: 0,980 kg/l
- Cut level: 2/10
- Gloss level: 10/10
- Color: white
- Fragrance: characteristic
- Solubility: miscible in water

**APPLICATION**

- Before application surface must be dry.
- Apply small quantity on the surface to be treated (polish small area at a time).
- Polish the surface with soft polishing sponge applying medium pressure.
- Reduce pressure to achieve the intended effect.
- After polishing leave the product for about 30 – 60 min. to create protection.
- Remove any residue with microfiber cloth or orbital polisher with soft polishing sponge.
- Don't use on unpolymerized surface.

**STORAGE**

Product works best when its temperature is 15 – 25°C.

Storage in sealed container at 0 – 45°C.

**WARRANTY PERIOD**

18 months from production date.

All information are based upon the precise laboratory studies and many years of experience. The good market position does not release us from the constant supervision of our products quality. However we are not responsible for the final effects of the improper storage or application of our products, as well as for work inconsistent with the good craft practice.

TROTON Sp. z o.o.

**TROTON Sp. z.o.o**

Address: Ząbrowo 14A, 78-120 Gościno, Poland, Tel: +48 94 35 123 94  
Tel/Fax: +48 94 35 126 22 Website: [www.troton.com.pl](http://www.troton.com.pl) Email: [troton@troton.com.pl](mailto:troton@troton.com.pl)



**January 2018**

Ząbrowo, Poland

---

**TROTON Sp. z.o.o**

**Address:** Ząbrowo 14A, 78-120 Gościno, Poland, **Tel:** +48 94 35 123 94  
**Tel/Fax:** +48 94 35 126 22 **Website:** [www.troton.com.pl](http://www.troton.com.pl) **Email:** [troton@troton.com.pl](mailto:troton@troton.com.pl)