

Issue date: May 2017

Superseded: September 2015

Kapci 460 NC Surfacer

Product properties

Kapci 460 is a fast drying and easy sandable nitrocellulose surfacer with good filling properties. It is used for wooden surfaces not exposed to mechanical, chemical, or thermal effects. Kapci 460 can be used for furniture, wooden articles and interior woodwork including cupboards, shelves, door frames, window frames, partitions, etc.

Theoretical coverage: 5-7 m²/kg per a coat

Products for application

Kapci 460 NC Surfacer Kapci 525 NC Thinner

Substrate and surface preparation

Sand the surface of solid wood with P80 or P120 sanding paper. Blow off dust and wipe off contaminants (grease, oil, etc.) prior to applying Kapci 460 NC surfacer.

Mixing ratio by weight

Kapci 460 NC Surfacer 100% Kapci 525 NC Thinner max 80%

Application

Kapci 460 NC Surfacer is applied by spraying in 2 coats.

Drying time at 25°C

Dry dust free: 20-30 min Dry to sand: 2-4 h



Issue date: May 2017

Superseded: September 2015

Other tips

- 1. Practical coverage depends on several factors including shape, roughness and porosity of the object to be painted, spraying equipment used, application methods, application conditions, film thickness, etc.
- 2. For best results, it is always recommended to test the products on scrap pieces of wood before start paint job.

Shelf life

3 years from production date stored in original packaging at normal conditions.

Health and Safety

- 1. For full Health and Safety information please refer to the Material Safety Data Sheet.
- 2. Observe the precautionary notices displayed on the container.
- 3. Good ventilation must be provided in the working environment.

IMPORTANT NOTE: The information in this technical data sheet is based on our best knowledge and given for information purposes only without any obligation as we do not have control over the quality and conditions of the surface, or over many factors affecting the use and the application of the product. Always read the Materials Safety Data Sheet and the Technical Data Sheet for this product if available.