

Walplast®

BUILDWELL

GYPSUM PLASTER

MILAYE
SIRF PAANI
LAGAYE BINA
PARESHAANI™




25 Kg Bag | PACKAGING


Highlights

- ✓ Superior Whiteness
- ✓ No Shrinkage Cracks
- ✓ Imparts High Coverage
- ✓ No Water Curing Required

HOW TO APPLY




1 Clean the surface with sand paper/wire brush & then dampen it.




2 Use 1 part water & 1.5 part of Gypsum plaster.



3 Mix Buildwell Gypsum plaster in water to form uniform lump free paste.



4 Install the wooden strip / dhada or the leveling strip in the area where the ready paste is to be applied.



5 Apply the first coat approx upto 8 mm to 10 mm of thickness, before the 1st coat sets rake and cross rake the surface.



6 After drying for 72 hrs surface is now ready for painting.

TECHNICAL INFORMATION

PARAMETER	TEST METHOD	SPECIFICATION	RESULTS
Whiteness %	IS: 8042-1989	89 - 91	90.2
Workability	Internal	Good	Good
Residue on 200 mesh %	Internal	<3	0.9
Setting Time Min.	Internal	13-15	14

TECHNICAL SPECIFICATION

Appearance	Superior Whiteness
Pot Life	25 – 30 minutes
Coverage @ thickness of 10 mm.	20 – 25 Sq.ft./Bag of 25 Kg

KEY FEATURES

- Faster setting than the conventional sand cement plaster
- 50% lighter than sand cement plaster, reduces structural load on the building
- Direct application
- Compatible with all types of paints & decoratives
- Lowers paint consumption



STORAGE



Walplast Products Pvt. Ltd. ISO 9001 : 2015 Certified Company

Corporate Office: Rainbow Building, Plot No. 13, Sector - 24, Mumbai Pune Highway Service Road, Turbhe, Navi Mumbai - 400 705, Maharashtra, India. **Tel no.:** 022-41418282. **Enquiry No.:** 1800 3000 6650

Email: sales@walplast.com, customercare@walplast.com / **For more details visit us at:** www.walplast.com

Disclaimer: The product information and application details given by the company and its agents has been provided in good faith and meant to serve only as a general guideline during usage. Users are advised to carry out test and take trials to ensure on the suitable of the products meeting their requirement prior to the full scale usage of our products. Since the correct identification of the problems, quality or other materials used and the on-site workmanship are factors beyond our control, there are no guarantee/warranty as to the result obtained. The company does not assure any liability for unsatisfaction results arising from the use of our products.