

FLOOR DRESSING PAINT

DESCRIPTION

A Styrenated alkyd-based floor dressing paint. Use as protective coating on concrete floors. Available in wide range of colors.

USAGE

For interior use on concrete floors for light traffic.

APPLICATION

- Apply two coats by roller or brush onto clean, dry and grease free surface.
- First coat must thin down more than the second coat.
- Low pressure or airless spray equipment can also be used.

MIXING RATIO *(Dilute with Slow Aromatic Solvent)*



* (Floor Dressing : Slow Aromatic Solvent)

TECHNICAL DATA (@ 25°)

Specific Gravity	~1.15
Volume Solids	~50%
Viscosity	~3500cP
Finish	Satin
Coverage	~ 10 m ² / L
Packaging	1 L, 5 L, 20 L

SURFACE PREPARATIONS

Wash surface with water under high pressure, let dry, and then apply two coats of FLOOR DRESSING.

Note: Peeling off of the coating may occur if substrate contains water. This is due to high vapor pressure build up in the substrate. The use of Chlorinated Sealer is recommended to reduce this occurrence.

DRYING TIME

Approximately 6h to touch dry can be over-coated after approximately 12h.

STORAGE

- Tightly closed container should be kept in a cool, dry place.
- Sealed product can be stored for over 2 years.

CLEANING

Use Aromatic Solvent.

SAFETY

- Ensure good ventilation during application and drying. Avoid eating, drinking and smoking while painting.
- In case of contact with eyes, wash with ample water and seek medical advice if necessary.
- Keep out of reach of children.
- Do not use empty containers to store food.
- Do not throw away in waterway.

DISCLAIMER

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.