

DESCRIPTION

High quality copolymer acrylic white paint, being odorless, having good opacity and coverage which conforms to Quality Standard MS3 of the Mauritius Standard Bureau. Product is suitable for interior and exterior decoration.


USAGE

Recommended for interior and exterior use in dry regions. Only for interior use in humid regions.

APPLICATION

Apply two coats by roller or brush onto clean, dry and sealed surface.

MIXING RATIO *(Dilute with water)*



* (Pure White : Water)

TECHNICAL DATA *(at 25°C)*

Specific Gravity	~ 1.50
Opacity 120 µm wet	98%
Volume Solids	~ 40%
Viscosity	~ 18000 cP
VOC	< 1 g/L
Finish	Matt
Coverage	~ 12 m ² /L/ coat
Packaging	1 L, 2.5 L, 5 L, 20 L

CLEANING

Use water; however do not throw away in waterway.

SURFACE PREPARATIONS

- For concrete and plaster, wash surface with water under high pressure, let dry, then apply one thin coat of Wall Primer (<50 µm).
- If the old coating and/or its substrate have blisters or other defects, it would indicate that total removal of the old coating is advisable. Remove by mechanical means or by stripping with Paint Remover. On powder old coatings, apply 1 coat WALL PRIMER.

If substrate shows presence of fungi or algae, please proceed with the following surface preparations:

- Apply FUNGICIDAL WASH by roller and leave to react for 12h minimum. Rinse with high pressure water again. Brush if necessary. Once dried, apply a coat of Fungicidal Treatment on the surface which will be coated the same day. Apply a thin coat of WALL PRIMER where necessary and leave to dry for 3h minimum. Apply 2 coats of PURE WHITE paint, leaving each coat to dry 3h minimum.

DRYING TIME

Approximately 1h to touch dry; can be over-coated after approximately 4h.

STORAGE

Container should be kept in a cool, dry and well-ventilated place. Container must be tightly closed after use. Sealed product can be stored for over 1 year.

SAFETY

- Ensure good ventilation during application and drying. Avoid eating, drinking and smoking while painting.
- In case of insufficient ventilation, wear suitable respiratory equipment.
- In case of contact with eyes, wash with ample water and seek medical advice if necessary.
- Keep out of reach of children.
- Do not use empty containers to store food.
- Do not throw away in waterway.

DISCLAIMER

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.