

DESCRIPTION

Polytol Water-Based Metal Primer is an anti-corrosive water-borne primer that is manufactured from high-quality pigments and special acrylic resin. It has excellent anti-corrosion and adhesion properties. Available in red and grey.


USAGE

It is suitable for priming ferrous and non-ferrous metals and can be applied directly over a lightly rusted coating. It is fast drying & easy to apply, ideal for both interior & exterior applications.

APPLICATION

Apply 1 coat by brush onto suitably treated surface.

MIXING RATIO *(Dilute with Water)*



* (Water-based Metal Primer : Water)

TECHNICAL DATA *(at 25°C)*

Finish	Satin
Coverage	~ 10 m ² / L
Opacity 120 µm wet	100 %
Specific Gravity	~1.00
Volume Solids	30%
Viscosity	~8000 cP
Packaging	1L , 5L

SURFACE PREPARATIONS

Ensure all surfaces are clean, dry and free from grease, oil, sandable rust and any other contaminants.

DRYING TIME

Approximately 1h to touch dry; can be over-coated after approximately 2h.

STORAGE

- Tightly closed container should be kept in a cool, dry place.
- Sealed product can be stored for over 1 year.

CLEANING

Use water, however do not throw away in waterway.

SAFETY

- Ensure good ventilation during application and drying. Avoid eating, drinking and smoking while painting.
- In case of contact with eyes, wash with ample water and seek medical advice if necessary.
- Keep out of reach of children.
- Do not use empty containers to store food.
- Do not throw away in waterway.

DISCLAIMER

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.