

TECHNICAL DATASHEET

WATERPROOFING CRACK FILLER

WATERPROOFING CRACK FILLER is a high-performance, versatile solution designed to repair and restore cracked surfaces in various applications, including concrete, masonry and asphalt. Its advanced formulation ensures durability, flexibility and ease of use, making it an ideal choice for both DIY enthusiasts and professionals.

KEY FEATURES

- **Flexible:** The filler helps in bridging hairline cracks up to 2mm.
- **Fast Curing:** Dries quickly, enabling efficient project completion with minimal downtime.
- **Easy Application:** Designed for effortless application with a putty knife. **Waterproofing Crack Filler** adheres well to surfaces, ensuring a smooth finish.
- **Weather Resistant:** Provides excellent resistance to moisture, UV rays and harsh weather conditions, making it suitable for both indoor and outdoor use.
- **Paintable and Stainable:** Once cured, the filler can be easily painted or stained to match the surrounding surface, ensuring a seamless repair.
- **Environment Friendly:** Made with non-toxic materials, it is safe for use in residential and commercial spaces.
- **Waterproof:** Creates a barrier against moisture.
- **Easy to Apply:** Usually comes in a ready-to-use format.
- **Durable:** Long-lasting protection against water damage.

APPLICATION

- Repairing cracks in concrete driveways, sidewalks and patios.
- Filling gaps in brick and masonry walls & hairline cracks.

TECHNICAL DATA

Product	Waterproofing crack filler.
Binders	Acrylic polymer with fibers
Dilution	With water if required.
Available Pack	1 Kg and 5 Kg
Shelf-life	Store containers in a clean dry area away from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.
Available Color	Off-White
Coverage	≈ 1.5 kg/ m ²
Surface Drying Time	30 minutes @ 25°C

PREPARATION OF SURFACE

Ensure that all dust, dirt and foreign matter are scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges, and protect all adjacent surfaces not to be covered.

POST PAINTING CARE

- **Surface Preparation:** Ensure surface is clean, dry and free from dust, grease and loose materials.
- **Application Method:**
 - Apply Durabond A in cracks using a brush and let dry for 2h.
 - Apply filler using a putty knife or trowel.
 - For deep cracks, multiple applications may be required.

PRECAUTIONS

- For the best performance of the paint, at regular intervals of six months a proper washing and cleaning of all algae and fungal growth must be carried out, if any.

SAFETY FEATURES

- Store the container with the tightly closed lid in an upright position, in a cool and dry place.
- Keep out of reach of children and away from eating tables.
- May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapor or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Do not pour leftover paint down the drain or in water courses.
- In an event of spill, contain spillage using sand or earth.
- No added Lead, Mercury or Chromium compounds.

DISCLAIMER

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.