

Polybois

ACID CATALYST VARNISH 2 PACK

DESCRIPTION

A combination of Alkyd and Urea Formaldehyde resin based varnish for wood. Available in gloss and satin finish. Low odour, quick drying and having good scratch resistance.

USAGE

For use as decorative and protective coating on wooden surfaces. Interior use.

APPLICATION

Apply two coats by spray onto clean, dry and grease free surface.

MIXING RATIO

Varnish : Acid
20 : 1 *or* 5% acid to varnish

TECHNICAL DATA

Specific Gravity	~ 1.00
Volume Solids	~ 50%
Viscosity	400 - 600 cP / 25°C
Finish	Gloss / Satin
Coverage	~ 10m ² per L
Packing	1 L, 5 L, 20 L

SURFACE PREPARATIONS

Clean surface then apply two coats of Nitro Sanding Sealer. Sand in between coats. Let dry then sand down with medium sanding paper.

Apply two coats of Acid Catalyst Varnish.

DRYING TIME

Dust dry	30 min approximately at 25°C
Touch dry	1 hours approximately at 25°C
Hard dry	2 hours approximately at 25°C

STORAGE

- Tightly closed container should be kept in a cool, dry place.
- Sealed product can be stored for over 1 year.

CLEANING

Use NC Thinner.

SAFETY

- Ensure good ventilation during application and drying. Avoid eating, drinking and smoking while painting.
- In case of contact with eyes, wash with ample water and seek medical advice if necessary.
- Keep out of reach of children.
- Do not use empty containers to store food.
- Do not throw away in waterway.

DISCLAIMER

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.