

# ALKYD UNDERCOAT

## DESCRIPTION

Alkyd and solvent based white undercoat with good filing properties.


## USAGE

- On cement substrates such as plaster, concrete, plaster board, old paint and building blocks.
- On ceiling boards and interior panel wood.
- Recommended for interior and exterior use.

## APPLICATION

Apply one coat by brush onto clean and dry surface. Low pressure or airless spray equipment can also be used.

## MIXING RATIO *(Dilute with White Spirit)*



## TECHNICAL DATA

|          |                            |
|----------|----------------------------|
| Finish   | Matt                       |
| Coverage | ~ 10 m <sup>2</sup> / L    |
| Packing  | 250ML, 500ML, 1 L, 2L, 5 L |

## DRYING TIME

Approximately 5-6h to touch dry can be over-coated after approximately 9-10h.

## CLEANING

Use White Spirit.

## SURFACE PREPARATIONS

- For concrete and plaster, wash surface with water under high pressure, let dry, then apply one full coat of ALKYD UNDERCOAT.
- For timber, make sure that the surface is clean, dry then apply one thin coat of ALKYD UNDERCOAT.
- If the old coating and/or its substrate have blisters or other defects, then total removal of the old coating must be done by mechanical means or by stripping with paint remover. On powder old coatings, apply 1 coat Clear Binder.
- For wood, apply one coat of ALKYD UNDERCOAT on a sealed surface.

**If substrate shows presence of fungi or algae, please proceed with the following surface preparations:**

- Apply fungicidal wash by roller and leave to react for 12h minimum. Rinse with high pressure water again. Brush if necessary. Once dried, apply a coat of fungicidal treatment on the surface which will be coated the same day. Apply a full coat of Clear Binder where necessary and leave to dry for 3h minimum. Apply 1 coat of ALKYD UNDERCOAT, leaving to dry 6h minimum.

## STORAGE

- Tightly closed container should be kept in a cool, dry place.
- Sealed product can be stored for over 2 years.

## SAFETY

- Ensure good ventilation during application and drying. Avoid eating, drinking and smoking while painting.
- In case of contact with eyes, wash with ample water and seek medical advice if necessary.
- Keep out of reach of children.
- Do not use empty containers to store food.
- Do not throw away in waterway.

### DISCLAIMER

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.