

Polybois

DESCRIPTION

Alkyd resin varnish for wood, cross linked with urethane functional groups. Available in gloss and satin finish. Has excellent resistance to scratching, weathering and yellowing.

USAGE

For use as decorative and protective coating on wooden surfaces. Good for parquet varnishing. Interior and exterior use.

APPLICATION

Apply two coats by roller, spray or brush onto clean, dry and grease free surface.

MIXING RATIO *(Dilute with White Spirit)*



TECHNICAL DATA

Specific Gravity	~ 0.90
Volume Solids	~ 34%
Viscosity	1200 - 1500 cP / 25°C
Finish	Gloss / Satin
Coverage	~ 12m ² per L
Packing	1 L, 5 L, 20 L

ALKYD URETHANE VARNISH

SURFACE PREPARATIONS

Clean surface then apply two coats of **Nitro Sanding Sealer**. Sand in between coats. Let dry then sand down with medium sanding paper.

Apply two coats of **Alkyd Urethane Varnish**.

DRYING TIME

Dust dry	15-20 min approximately at 25°C
Touch dry	2 hours approximately at 25°C
Hard dry	16 hours approximately at 25°C

STORAGE

- Tightly closed container should be kept in a cool, dry place.
- Sealed product can be stored for over 1 year.

CLEANING

Use Aromatic Thinner

SAFETY

- Ensure good ventilation during application and drying. Avoid eating, drinking and smoking while painting.
- In case of contact with eyes, wash with ample water and seek medical advice if necessary.
- Keep out of reach of children.
- Do not use empty containers to store food.
- Do not throw away in waterway.

DISCLAIMER

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.