

CHLORINATED FLOOR DRESSING PAINT

DESCRIPTION

- Chlorinated floor dressing paint is based on copolymer of vinyl chloride. Use as protective coating on concrete floors.
- It shows good weathering resistance.
- It is available in wide range of colors.

USAGE

For interior and exterior use on concrete and floors for medium traffic purpose.

APPLICATION

Apply 2 coats by roller or brush onto clean, dry and grease free surface. Low pressure or airless spray equipment can also be used.

Note: Peeling off of the coating may occur if substrate contains water. This is due to high vapor pressure build up in the substrate. The use of Chlorinated Sealer is recommended to reduce this occurrence.

MIXING RATIO (Dilute with Slow Aromatic Solvent)



TECHNICAL DATA

| | |
|----------|-------------------------|
| Finish | Satin |
| Coverage | ~ 10 m ² / L |
| Packing | 1 L, 5 L, 20 L |

SURFACE PREPARATIONS

Wash surface with water under high pressure, let dry for 24h, and then apply one coat of CHLORINATED SEALER. Let it dries overnight and then apply two coats of Chlorinated Floor dressing Paint.

DRYING TIME

Approximately 1h to touch dry, can be over-coated after approximately 4h.

STORAGE

- Tightly closed container should be kept in a cool, dry place.
- Sealed product can be stored for over 2 years.

CLEANING

Use Aromatic Solvent.

SAFETY

- Ensure good ventilation during application and drying. Avoid eating, drinking and smoking while painting.
- In case of contact with eyes, wash with ample water and seek medical advice if necessary.
- Keep out of reach of children.
- Do not use empty containers to store food.
- Do not throw away in waterway.

DISCLAIMER

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.