

CHLORINATED ROAD MARKING PAINT

DESCRIPTION

Road marking paint is a quick drying durable solvent borne paint. Various properties of the paint include resistance to cold water, diesel fuel.

USAGE

- For bituminous and concrete road surfaces.
- Suitable for line marking use on highways, parking lots and factory floors.
- For interior and exterior use.

APPLICATION

Apply two coats by roller or brush. Low pressure or airless spray equipment can also be used.

MIXING RATIO *(Dilute with Aromatic Solvent)*

Dilute with aromatic solvent if necessary (Depending on applicator).

TECHNICAL DATA

	WHITE	BLACK	YELLOW
Specific Gravity	1.45	1.15	1.41
Volume Solids	Matt	Matt	Matt
Shelf Life	12 months		
Packing	1 L, 5 L, 20 L		

SURFACE PREPARATIONS

The substrate must be clean, dry, and free from dust, oil, grease.

STORAGE

- Tightly closed container should be kept in a cool, dry place.
- Sealed product can be stored for over 1 year.

CLEANING

Use Aromatic Solvent.

SAFETY

- Ensure good ventilation during application and drying. Avoid eating, drinking and smoking while painting.
- In case of contact with eyes, wash with ample water and seek medical advice if necessary.
- Keep out of reach of children.
- Do not use empty containers to store food.
- Do not throw away in waterway.

DISCLAIMER

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.