

## DESCRIPTION

Transparent co-polymer acrylic emulsion sealer. Penetrates the substrate to give good adhesion of subsequent coatings.

## USAGE

For use on powdered and weathered coatings.

## APPLICATION

Apply one coat by roller or brush onto clean, dry surface.

## MIXING RATIO

Not necessary.

## TECHNICAL DATA

Specific Gravity	~ 1.00
Volume Solids	~ 55%
Finish	Transparent
Coverage	~ 14 m <sup>2</sup> per L
Packing	1 L, 5 L, 20 L

## DRYING TIME

Approximately 1h to touch dry.

## SURFACE PREPARATIONS

- If the old coating and/or its substrate have blisters or other defects then total removal must be done by mechanical means or by stripping with paint remover. On powder old coatings, apply 1 coat Clear Binder.

If substrate shows presence of fungi or algae, please proceed with the following surface preparations:

- Apply fungicidal wash by roller and leave to react for 12h minimum. Rinse with high pressure water again. Brush if necessary. Once dried, apply a coat of fungicidal treatment on the surface which will be coated the same day. Apply a thin coat of Clear Binder where necessary and leave to dry for 3h minimum.

## STORAGE

- Tightly closed container should be kept in a cool, dry place.
- Sealed product can be stored for over 2 years.

## CLEANING

Use water; however do not throw away in waterway.

## SAFETY

- Ensure good ventilation during application and drying. Avoid eating, drinking and smoking while painting.
- In case of contact with eyes, wash with ample water and seek medical advice if necessary.
- Keep out of reach of children.
- Do not use empty containers to store food.
- Do not throw away in waterway.

### DISCLAIMER

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.