

DESCRIPTION

Primer based on polyvinyl butyral resin formulated to give a good first adhesive coat on galvanized substrate and corrosion protection.

USAGE

For use on metallic rust free surfaces and galvanized substrate.

APPLICATION

Apply 1 coat by brush onto suitably treated surface. Do not use any polyester coating either under or over Etch Primer.

MIXING RATIO *(Dilution not required*)*



* Dilute with IPA if necessary.

TECHNICAL DATA

Finish	Matt
Pot Life	4h
Coverage	~ 10 m ² / L
Packing	500 ML, 1 L, 5 L

SURFACE PREPARATIONS

- Remove all traces of rust, and then apply one coat of 2 PACK ETCH PRIMER.
- Product should imperatively be in no direct contact with Polytol Car Body Filler.

DRYING TIME

Approximately 15 min to touch dry; can be over-coated after approximately 1h.

STORAGE

- Tightly closed container should be kept in a cool, dry place.
- Sealed product can be stored for over 2 years.

CLEANING

Use NC Thinner.

SAFETY

- Ensure good ventilation during application and drying. Avoid eating, drinking and smoking while painting.
- In case of contact with eyes, wash with ample water and seek medical advice if necessary.
- Keep out of reach of children.
- Do not use empty containers to store food.
- Do not throw away in waterway.

DISCLAIMER

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.