

## DESCRIPTION

Copolymer acrylic paint, having good opacity and coverage. Available in white, pastel and mid-basic colours as per our POLYMATCH SYSTEM.

## USAGE

Recommended for interior use only.

## APPLICATION

Apply two coats by roller or brush onto clean, dry and sealed surface.

## MIXING RATIO *(Dilute with water)*



## TECHNICAL DATA

Specific Gravity	~ 1.5
Opacity 120 µ wet	~ 97%
Volume Solids	~32%
Finish	Matt
Coverage	~ 10 m <sup>2</sup> /L
Packing	1L, 2L, 5 L, 20 L

## CLEANING

Use water; however do not throw away in waterway.

## SURFACE PREPARATIONS

- For concrete and plaster, wash surface with water under high pressure, let dry, then apply one thin coat of Wall Primer (<50 µm).
- If the old coating and/or its substrate have blisters or other defects, then total removal must be done by mechanical means or by stripping with paint remover. On powder old coatings, apply 1 coat POLYCOLOR CLEAR BINDER.

**If substrate shows presence of fungi or algae, please proceed with the following surface preparations:**

- Apply POLYCOLOR FUNGICIDAL WASH by roller and leave to react for 12h minimum. Rinse with high pressure water again. Brush if necessary. Once dried, apply a coat of POLYCOLOR FUNGICIDAL TREATMENT on the surface which will be coated the same day. Apply a thin coat of POLYCOLOR CLEAR BINDER where necessary and leave to dry for 3 hours minimum. Apply 2 coats of POLYCOLOR FLAT VINYL paint, leaving each coat to dry 3 hours minimum.

## DRYING TIME

Approximately 1h to touch dry; can be over-coated after approximately 4h.

## STORAGE

Tightly closed container should be kept in a cool, dry place. Sealed product can be stored for over 2 year.

## SAFETY

- Ensure good ventilation during application and drying. Avoid eating, drinking and smoking while painting.
- In case of insufficient ventilation, wear suitable respiratory equipment.
- In case of contact with eyes, wash with ample water and seek medical advice if necessary.
- Keep out of reach of children.
- Do not use empty containers to store food.
- Do not throw away in waterway.

### DISCLAIMER

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.