

DESCRIPTION

An alkyd resin based primer having good anticorrosive properties.

USAGE

For use on new or weathered metallic galvanized surfaces.

Always apply etch primer on bare galvanized substrates.

APPLICATION

Apply 1 coat by brush onto suitably treated surface.

MIXING RATIO *(Dilute with White Spirit)*



TECHNICAL DATA

Finish	Matt
Coverage	~ 10 m ² / L
Packing	250ML, 500ML, 1 L, 2L, 5 L

SURFACE PREPARATIONS

Clean and degrease before applying primer.

For new or weathered galvanized substrate applied one coat of Etch Primer before application of Galva Primer.

DRYING TIME

Approximately 1h to touch dry; can be over-coated after approximately 4h.

STORAGE

- Tightly closed container should be kept in a cool, dry place.
- Sealed product can be stored for over 2 years.

CLEANING

Use White Spirit.

SAFETY

- Ensure good ventilation during application and drying. Avoid eating, drinking and smoking while painting.
- In case of contact with eyes, wash with ample water and seek medical advice if necessary.
- Keep out of reach of children.
- Do not use empty containers to store food.
- Do not throw away in waterway.

DISCLAIMER

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.