

## DESCRIPTION

A premium grade alkyd finish for both decorative and protective purpose on metallic and wooden surfaces. Specially formulated both either interior or exterior applications. The dry film of G.P. ALUMINIUM gives a tough, washable and lightfast finish which is impermeable to liquids and light. Any wooden or metallic surface coated with G.P. ALUMINIUM is therefore guaranteed to be anti-corrosive and a good sealer.

## USAGE

Recommended for exterior use in humid and dusty regions.

## APPLICATION

- Apply 2-3 coats by roller or brush on clean, dry and appropriately primed metallic surfaces.
- Short-fibre rollers give better uniformity for large flat surfaces.
- On wood, apply 1 coat by brush for sealing.

## MIXING RATIO *(Dilute with White Spirit)*



## TECHNICAL DATA

Specific Gravity	~ 0.95
Volume Solids	~ 46%
Finish	Metallic Gloss
Coverage	~ 15 m <sup>2</sup> per L
Packing	250 ML, 500 ML, 1 L, 5 L

## DRYING TIME

Approximately 4h to touch dry can be over-coated after approximately 16h.

## SURFACE PREPARATIONS

- For new wood, apply one coat of NC SEALER followed by one coat of ALKYD UNDERCOAT.
- For old coatings on wood, remove coating completely with sanding paper or paint remover.
- For metallic surfaces, apply one coat of suitable primer on a non-rusted and dry surface. In case of presence of rust, use POLYTOL RUST REMOVER.
- In case of old coating and/or loose paints on surface, total removal must be done by mechanical means or by stripping with paint remover.
- For substrates that are affected by fungi and algae attack, FUNGICIDAL WASH by roller should be applied and left to react for 12 h minimum. Rinse with high pressure water and brush if necessary to ensure complete elimination of algae & fungus.

## STORAGE

- Keep in a cool, dry place. Close container tightly after use.
- Sealed product can be stored for over 1 year.

## CLEANING

Use NC Thinner/ Slow Aromatic Solvent.

## SAFETY

- Ensure good ventilation during application and drying.  
Avoid eating and drinking while using product.
- Keep away from heat source, open flame and avoid smoking while using product.
- In case of contact with eyes, rinse immediately with water and seek medical advice if necessary.
- Keep out of reach of children.
- Do not use empty containers to store food.
- Do not throw away in waterway or environment.

### DISCLAIMER

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.