



NC PRIMER FILLER

DESCRIPTION

Spraying nitro synthetic primer filler, designed with the properties of good drying, filling, adhesion, easy application, good sanding ability and excellent protection against corrosion. Available in white, grey and yellow colours.

USAGE

For use on Polytol Car Body Filler or Nitro Cellulose Stopper. For use as primer on wooden and rust free metallic surfaces.

APPLICATION

Apply two coats by brush or spray on clean and dry surface.

MIXING RATIO *(Dilute with NC Thinner)*

Dilute with NC Thinner to viscosity DIN 4 at 20°C around 18 – 20 seconds.

2 Part Nc Primer Filler: 1 Part Thinner

TECHNICAL DATA

Specific Gravity	~ 1.20
Volume Solids	~ 37%
Finish	Matt
Packing	1 L, 5 L, 20 L

DRYING TIME

Dust dry	Approximately 5 min
Touch dry	Approximately 10 min
Sandable	Approximately 30 min

STORAGE

- Tightly closed container should be kept in a cool, dry place.
- Sealed product can be stored for over 1 year.

CLEANING

Use NC Thinner.

SAFETY

- Ensure good ventilation during application and drying. Avoid eating, drinking and smoking while painting.
- In case of contact with eyes, wash with ample water and seek medical advice if necessary.
- Keep out of reach of children.
- Do not use empty containers to store food.
- Do not throw away in waterway.

DISCLAIMER

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.