



NITRO CELLULOSE PAINTS

DESCRIPTION

A Nitro synthetic fast drying paint with good weather resistance. Available in white, black, bright, basic and pastel shades.

USAGE

For use on wooden and metallic surfaces.

APPLICATION

Apply two coats by spray on primed, clean and dry surface.

MIXING RATIO *(Dilute with NC Thinner)*

Dilute with NC Thinner to viscosity DIN 4 at 20°C around 18 – 20 seconds.

TECHNICAL DATA

Specific Gravity	~ 1.00
Volume Solids	~ 30%
Viscosity	2200 - 2500 cP / 25°C
Finish	Gloss / Satin / Matt
Packing	1 L, 5 L, 20 L

SURFACE PREPARATIONS

Sand down primer or old coatings with sand paper P400-P600, then apply two full coats.

STORAGE

- Tightly closed container should be kept in a cool, dry place.
- Sealed product can be stored for over 1 years.

CLEANING

Use NC Thinner.

SAFETY

- Ensure good ventilation during application and drying. Avoid eating, drinking and smoking while painting.
- In case of contact with eyes, wash with ample water and seek medical advice if necessary.
- Keep out of reach of children.
- Do not use empty containers to store food.
- Do not throw away in waterway.

DRYING TIME

Dust dry	Approximately 10 min
Touch dry	Approximately 30 min

DISCLAIMER

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.