



NITRO CELLULOSE STOPPER

DESCRIPTION

Knifing repair stopper based on a pigmented nitro cellulose base, and is designed with the properties of good drying, filling, adhesion, easy application and good sanding ability. Available in brown and white.

USAGE

Used on Polytol Car Body Filler to hide small indents.

APPLICATION

Apply using plastic spatula in thin layers at 5 minutes interval.

MIXING RATIO *(Dilute with NC Thinner)*

Dilute with NC Thinner to viscosity DIN 4 at 20°C around 18 – 20 seconds.

TECHNICAL DATA

Specific Gravity	~ 1.50
Finish	Matt
Packing	250 ML, 1 L

DRYING TIME

Approximately 6 h. Can be sanded after 12h.

SURFACE PREPARATIONS

Apply on surfaces sanded with P120 onwards.

STORAGE

- Tightly closed container should be kept in a cool, dry place.
- Sealed product can be stored for over 1 year.

CLEANING

Use NC Thinner.

SAFETY

- Ensure good ventilation during application and drying. Avoid eating, drinking and smoking while painting.
- In case of contact with eyes, wash with ample water and seek medical advice if necessary.
- Keep out of reach of children.
- Do not use empty containers to store food.
- Do not throw away in waterway.

DISCLAIMER

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.