

# Polybois

# NITRO CELLULOSE VARNISH

## DESCRIPTION

Nitro cellulose based varnish for wood. Quick drying high gloss varnish available in gloss, satin and matt finish.



## USAGE

For use as decorative and protective coating on wooden surfaces. Interior and exterior use.

## APPLICATION

Apply two coats by roller, spray or brush onto clean, dry and grease free surface.

## MIXING RATIO *(Dilute with NC Thinner)*



## TECHNICAL DATA

Specific Gravity	~ 0.94
Volume Solids	~ 40%
Viscosity	2000 - 2300 cP / 25°C
Finish	Gloss / Satin / Matt
Coverage	~ 10m <sup>2</sup> per L
Packing	1 L, 5 L, 20 L

## SURFACE PREPARATIONS

Clean surface then apply two coats of **Nitro Sanding Sealer**. Sand in between coats. Let dry then sand down with medium sanding paper.

Apply two coats of Nitro cellulose Varnish.

## DRYING TIME

Dust dry	15 min approximately at 25°C
Touch dry	1 hours approximately at 25°C
Hard dry	4 hours approximately at 25°C

## STORAGE

- Tightly closed container should be kept in a cool, dry place.
- Sealed product can be stored for over 1 year.

## CLEANING

Use NC Thinner.

## SAFETY

- Ensure good ventilation during application and drying. Avoid eating, drinking and smoking while painting.
- In case of contact with eyes, wash with ample water and seek medical advice if necessary.
- Keep out of reach of children.
- Do not use empty containers to store food.
- Do not throw away in waterway.

### DISCLAIMER

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.