

WATERPROOFING

DESCRIPTION

Acrylic copolymer and highly efficacious and flexible emulsion product supported with **Polytol** membrane to provide excellent and long lasting water proofing properties to a roof.

USAGE

Recommended for flat roof water proofing, re-water proofing over existing water proofing system.

APPLICATION

- Apply a thin coat of **Polycolor Waterproofing, Terrabond A** and water in the ratio 4:1:1 with a roller/brush.
- Apply a thick coat of waterproofing product with a roller/brush on the support.
- Bed the poly membrane into the wet coat by using a roller, avoiding the formation of wrinkles or bubbles.
- Once the first coat has dried sufficiently, apply a second coat of waterproofing (0.5 litre/m²) to ensure the membrane is completely saturated.
- When the second coat is dry, apply a final coat of the waterproofing.

MIXING RATIO *(Product is ready for application)**



* However, it can be diluted if necessary.

SURFACE PREPARATIONS

All surfaces must be clean, dry and free of all grease, oil or loose flaking particles.

DRYING TIME

Approximately 1h to touch dry can be over-coated after approximately 4h at a temperature of 25° C.

STORAGE

- Tightly closed container should be kept in a cool, dry place.
- Sealed product can be stored for over 2 years.

CLEANING

Use water; however do not throw away in waterway.

SAFETY

- Ensure good ventilation during application and drying. Avoid eating, drinking and smoking while painting.
- In case of contact with eyes, wash with ample water and seek medical advice if necessary.
- Keep out of reach of children.
- Do not use empty containers to store food.
- Do not throw away in waterway.

TECHNICAL DATA

Specific Gravity	~ 1.20
Volume Solids	~ 38%
Finish	Matt
Coverage	~ 10 m ² / L for total system
Packing	1 L, 5 L, 20 L

DISCLAIMER

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.