

# Polybois

## WOOD STAIN

### DESCRIPTION

Solvent-based tinted wood stains.

Available in 9 standard colours: Black, Brown, Mahogany, Sapélé, Teak, Yellow, Prune, Acajou and Dark Oak.

Available in 3 UV resistant colours: Sico Teak, Sico Wengé and Sico Brown.

### USAGE

For use on wooden surfaces. Interior use only. Except for the 3 UV resistant wood stains; can be used for interior and exterior applications.

### APPLICATION

Apply by spray or brush onto clean, dry and grease free surface.

### MIXING RATIO *(Dilute with NC Thinner)*

Not necessary. Dilute with NC Thinner to lower tinting strength.

### TECHNICAL DATA

Specific Gravity	~ 0.85
Packing	1 L, 5 L

### DRYING TIME

Approximately 5 to 10 minutes to dry.

### SURFACE PREPARATIONS

Clean surface then apply two coats of Nitro Sanding Sealer. Sand in between coats. Let dry then sand down with medium sanding paper.

Apply wood stain.

### STORAGE

- Tightly closed container should be kept in a cool, dry place.
- Sealed product can be stored for over 1 year.

### CLEANING

Use NC Thinner.

### SAFETY

- Ensure good ventilation during application and drying. Avoid eating, drinking and smoking while painting.
- In case of contact with eyes, wash with ample water and seek medical advice if necessary.
- Keep out of reach of children.
- Do not use empty containers to store food.
- Do not throw away in waterway.

#### DISCLAIMER

These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.