TECHNICAL DATASHEET

FLOOR DRESSING/ROAD MARKING - Waterbased

Polycolor Floor Dressing/Road Marking is water based, water-repellent, rapid-drying coating. It contains Titanium Dioxide and premium color-fast pigments. This specifically formulated product offers excellent resistance to abrasion, making it ideal for concrete and asphalt runway marking. It is designed for versatility and durability.

PRODUCT BENEFITS

- **Versatility:** Can be used on a variety of surfaces, Concrete, Asphalt, Paving blocks, Krebs.
- **Adhesion:** Provides excellent adhesion to most listed surfaces.
- **Color Retention:** Excellent color and gloss retention.
- **Resistance:** Excellent abrasion, chemical resistance and water resistance.
- **Application:** Can be used for interior and exterior applications.
- **Ease of Use:** User-friendly & Eco friendly with low Odor.
- **Flexibility:** Displays good flexibility and impact resistance.
- **Durability:** Ensures a long-lasting finish.
- **DIY concept:** Easy to apply on any substrate with recommended process.
- **Self-priming concept:** apply same paint as primer with dilution provide more good results.

PRODUCT FEATURES

Surface	Exterior and Interior
Available Pack	1L, 5L and 20L
Shelf life	2 years from date of manufacture in original tightly closed containers.
Available Color	White, Yellow, Blue, Red, L.B Grey & D.B Grey (customize shades on bulk order)
Coverage	Up to 11-12m^2/L/coat
Finish	Matt
Drying time to touch	30 Minutes @ 25 – 35°C

SURFACE PREPARATION

- Ensure surface is clean, dry and free from contaminants.
- Surface must be in good conditions without laitance.
- Remove laitance using wire brush or sweep blast.
- This product can be used as self-primer with 20% dilution as 1st coat and 2nd and 3rd coat as such.

APPLICATION PROCESS

Method	:	Brush and Roller
Thinning	:	Water
Dilution	:	Up to volume ratio (5:1) for 5 parts of paint & 1 part of water (for 1st coat) 2nd and 3rd coat as such.

POST PAINTING CARE

- For the best performance of the paint, at regular intervals of six months a proper washing and cleaning of all algae and fungal growth must be carried out, if any.

PRECAUTIONS

- Do not apply when ambient temperature is less than 5°C or if the temperature might drop to this level within 4 hrs of application.
- Do not apply it during rain or when rain is expected.
- Stir well before use.

SAFETY AND ENVIRONMENT FEATURES

- Store the container with the tightly closed lid in an upright position, in a cool dry place.
- Keep out of reach of children.
- May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapor or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Do not pour leftover paint down the drain or in water courses.
- In case of spillage, contain it using sand or earth.
- No added Lead, Mercury or Chromium compounds.

Left-Over paint disposal:

- Left-over paint/drums should not be disposed in soil/drains. Consumers should consult a local recycling agency for disposal of paint/drums.
- The pails/drums should not be used for storing food items.

DISCLAIMER
These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

Polytol Paints

Manufactured and Distributed by
Polytol Paints & Adhesives Mfg Co. Ltd
Baie du Tombeau Rd, Riche Terre
Tel 249 1299 / 249 1499 / Fax 248 3988