TECHNICAL DATASHEET

IZYCOLOR INTERIOR



IZY COLOR INTERIOR is a cost-effective interior paint designed to provide good coverage and opacity, It's a versatile option suitable for a variety of interior surfaces.

PRODUCT BENEFITS

- **Affordable: IZYCOLOR INTERIOR** offers a budget-friendly solution to paint your interior spaces.
- **Matt Finish:** Provides a flat, smooth and uniform finish which help to hide imperfections.
- **Excellent Coverage:** Offers superior coverage, often requiring fewer coats.
- **Cost-Effective:** The excellent coverage and durability can help to save money on paint costs.
- **Water-Based:** For a water-based paint, it has low-odor and environment friendly.

PRODUCT FEATURES

Surface	Interior use only.
Available Pack	5L, 20L
Shelf life	2 years from date of manufacture in original tightly closed containers. Keep away from direct sunlight and excessive heats.
Available Color	White
Coverage	14m^2/L/coat
Drying time to touch	30 Minutes @ 25°C/ Fast drying technology

HOW TO APPLY

- New masonry surfaces must be allowed to cure completely. It is recommended to **Allow 28 days as the curing time for new masonry surfaces.**

- In areas experiencing excessive dampness, underlying surface exhibits chalkiness use wire brushing, Polycolor Fungicidal Wash & Treatment and apply **Terraco Handycoat Interior** followed by 1 coat of **Polycolor Interior primer** and 2 – 3 coats **of IZYCOLOR INTERIOR PAINT**.

APPLICATION PROCESS

Method	:	Brush, Roller, Airless spray
Thinning	:	Water
Dilution	:	Up to volume ratio (3:1) 3 parts of paint & 1 part of water

TECHNICAL DETAILS

Drying Time	:	Surface dry time 30 mins
Recoat Application	:	After 2 - 4h
Finish	:	Matt
Volume Solid	:	Above 40%
Stability of Thinned Paint	:	To be used within 24h

POST PAINTING CARE

- Do not apply when ambient temperature is less than 5^0C or if the temperature might drop to this level within 4h of application.
- Do not over-thin or over-extend the brush.

PRECAUTIONS

- For the best performance of the paint, at regular intervals of six months a proper washing and cleaning of all algae and fungal growth must be carried out, if any.

SAFETY FEATURES

- Store the container with the tightly closed lid in an upright position, in a cool dry place.
- Keep out of reach of children.
- May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapor or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Do not pour leftover paint down the drain or in water courses.
- In case of spillage, contain it using sand or earth.
- No added Lead, Mercury or Chromium compounds.

DISCLAIMER
These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

Polytol Paints

Manufactured and Distributed by
Polytol Paints & Adhesives Mfg Co. Ltd
Baie du Tombeau Rd, Riche Terre
Tel 249 1299 / 249 1499 / Fax 248 3988