TECHNICAL DATASHEET

POLYCOLOR VIP SATIN



Polycolor VIP SATIN is a type of water base acrylic paint with **ultra-guard wax technology,** which is a **high-quality, luxury interior wall paint** known for its durability, colorfastness, and luxurious finish. It's designed to provide a smooth, even coat with a deep, rich color that gives **water beading technology**.

PRODUCT BENEFITS

- **Water-based:** Environment friendly and low odour.
- **Ultra-guard Wax Technology:** Protects the paint film and enhances durability.
- **Uniform film:** Creates a smooth and even finish.
- **Satin effect:** Offers a luxurious and elegant look.
- **Water beading technology:** Repels water, helping to maintain the paint's appearance.
- **Washability:** Easily cleaned with mild detergent and water, making it ideal for high-traffic areas.
- **High Durability:** Resists scuffs and marks, ensuring long-lasting beauty.
- **Elegant Finish:** Provides a soft, luxurious look that enhances any room's ambiance.
- **Light Reflection:** Offers a satin finish that reflects light, making rooms appear brighter
- and more spacious.
- **Low VOC:** Environment friendly with low volatile organic compounds.
- **Odorless:** Minimizes paint smell during and after application.

PRODUCT FEATURES

Surface	Interior only
Available Pack	1L, 5L, and 20L
Shelf life	2 years from date of manufacture in original tightly closed containers. Keep away from direct sunlight and excessive heat.
Available Color	White, Pastel, Basic, and Deep basic
Coverage	12 - 14 m^2/L/1 coat
Drying time to touch	30 Minutes @ 25°C / Fast drying technology

HOW TO APPLY

- New masonry surfaces must be allowed to cure completely. It is recommended to **allow 28 days as the curing time for new masonry surfaces.**

- In areas experiencing excessive dampness, underlying surface exhibits chalkiness use wire brushing, Polycolor Fungicidal Wash & Treatment and apply 1-2 coat of **Terraco Handycoat Interior** depend on surfaces and apply 1 coat of Polycolor Interior wall primer and 2 – 3coat of **POLYCOLOR VIP SATIN PAINT.**

APPLICATION PROCESS

Method	:	Brush, Roller, Airless spray
Thinning with	:	Water
Dilution ratio	:	Up to volume ratio (3:1) 3 parts of paints and 1 part of water

TECHNICAL DETAILS

Drying Time	:	Surface dry time 30 min
Finish	:	Satin, Smooth, and Uniform
Volume Solid	:	Above 40%
Stability of Thinned Paint	:	To be used within 24h

POST PAINTING CARE

- Do not apply when ambient temperature is less than 5^0C or if the temperature might drop to this level within 4h of application.
- Do not over-thin or over-extend the brush.

PRECAUTIONS

- For the best performance of the paint, at regular intervals of six months a proper washing and cleaning of all algae and fungal growth must be carried out, if any.

SAFETY FEATURES

- Store the container with the tightly closed lid in an upright position, in a cool dry place.
- Keep out of reach of children and away from eating tables.
- May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapor or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Do not pour leftover paint down the drain or in water courses.
- In an event of spill, contain spillage using sand or earth.
- No added Lead, Mercury or Chromium compounds.

DISCLAIMER
These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

Tolytol Paints
Manufactured and Distributed by
Polytol Paints & Adhesives Mfg Co. Ltd
Baie du Tombeau Rd, Riche Terre
Tel 249 1299 / 249 1499 / Fax 248 3988