TECHNICAL DATASHEET

ALKYD FLOOR DRESSING

Polycolor Alkyd floor dressing is a protective coating, specifically designed for use on concrete floors. It forms a durable film that protects the surface from moisture and abrasion. Its excellent adhesion, chemical resistance, and long-term durability make it suitable for indoor only.

PRODUCT BENEFITS

- **Reduces Surface Dusting**- Seals the concrete surface, preventing the release of fine dust particles and improving cleanliness.
- **Improves Aesthetic Appearance**- Enhances the look of concrete floors with a smooth, uniform, and often glossy finish.
- **Fast Drying and Easy Application**- Can be applied with a brush, roller, or spray; dries quickly to reduce downtime.
- **Low Maintenance**-Coated surfaces are easy to clean and maintain, reducing up keep costs over time.

AREAS OF APPLICATION

- Commercial Buildings
- Basements and Utility Rooms
- Walkways and Corridors

PRODUCT FEATURES

Surface	Interior
Available Pack	1L, 5L and 20L
Shelf life	2 years from date of manufacture in original tightly closed containers.
Available Color	Wide range of colors
Coverage	10 m^2/L/ coat
Finish	Satin
Drying time to touch	60 Minutes @ 25 – 35 °C
Overcoat application	After 4 hours

SURFACE PREPARATION

- Wash surface with water under high pressure, let it dry for 24 hours.
- Then, apply two coats of chlorinated floor dressing paint.

APPLICATION PROCESS

Method	:	Brush, Roller and spray gun
Thinning	:	White Spirit for roller and brush / White Spirit for spray gun
Dilution by volume	:	5:1 (5 parts paint and 1 part White spirit) for roller and brush and 3:1 (3 parts paint and 1 part White Spirit) for spray gun.

APPLICATION

- Apply two coats by roller or brush on clean, dry and grease free surface.
- Low pressure or spray gun can also be used.

PRECAUTIONS

- Do not apply when ambient temperature is less than 5°C or if the temperature might drop to this level within 4 hrs. of application.
- Do not apply it during rain or when rain is expected.
- Stir well before use.

SAFETY AND ENVIRONMENT FEATURES

- Store the container with the tightly closed lid in an upright position, in a cool dry place.
- Keep out of reach of children and away from eating tables.
- May be harmful if swallowed. In case of ingestion seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact, immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapor or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Do not pour leftover paint down the drain or in water courses.
- In an event of spill, contain spillage using sand or earth.
- No added Lead, Mercury or Chromium compounds.

Left-Over paint disposal:

- Left-over paint/drums should not be disposed in soil/drains. Consumers should consult a local recycling agency for disposal of paint/drums.
- The pails/drums should not be used for storing food items.

DISCLAIMER
These recommendations are meant as a guide, no guarantee is implied since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

Polytol Paints

Manufactured and Distributed by
Polytol Paints & Adhesives Mfg Co. Ltd
Baie du Tombeau Rd, Riche Terre
Tel 249 1299 / 249 1499 / Fax 248 3988